


**INCREMENTAL
ENCODER**

I/44S

MINIATURE ENCODER, METALLIC STANDARD 'SIZE 18' CONTAINER,
'SERVO-MOUNT' INSTALLATION. HIGH MECHANIC STOUTNESS AND HIGH
PROTECTION TO OIL, WATER, MOISTURE.

Incremental
page: 01. 44S 1/2
data sheet . II 006 E00

Sized draw standard version: CV Measures without tolerance according to UNI ISO 2768-mk



TECHNICAL FEATURES AND POSSIBLE CONFIGURATIONS

- | | |
|--|---|
| <ul style="list-style-type: none"> - Base.....: ANODIZED ALUMINIUM (*) - Cover.....: ANODIZED ALUMINIUM (*) - Weight.....: 230 g - Shaft.....: Ø 6 STAINLESS STEEL (*) - Max.rad/axial load.: 1,5 kg - IP output side.(°).: see 'CONNECTION' of page 2 - IP shaft side.(°).:> std. 66 sealed - low torq. 53 - opt. type (page 2).:> standard B - Contin. max RPM(**).:> 3000 - 12000 - Starting torque gcm>.:> 30 - 8 | <ul style="list-style-type: none"> - Ball bearings life....: 1,5 x 10⁹ revolutions - Impact resistance....: 50 G x 11ms - Vibration resistance..: 12 G (10 ÷ 2000 Hz) - Power supply.....: 5÷30V (see page 2) - Operating temperature.: 0 ÷ 70 °C (*) - Storage temperature...: -30 ÷ 85 °C - N° of pulses/rev.....: 1 ÷ 2540 - Max frequency.....: 60 kHz (100 option) - Max consumptions mA..: std 120 line driver 180 (*) - Light source.....: LED with >= 100000 h life |
|--|---|

(°) IP according to CEI EN 60529, EN 60529, IEC 529


(*) custom options

(**) intermittent max RPM + 30% of continuous max RPM


ELECTRONICS

CODE	DESCRIPTION	mA	CODE	DESCRIPTION	mA	CODE	DESCRIPTION	mA	CODE	DESCRIPTION	mA
K	STANDARD NPN	10	N	DRIVER 26LS31	30						
Q	NPN OPEN COLL	10	T	TTL 7404	10						
R	NPN OPEN COLL	70	C	DRIVER 88C30	20						
P	PNP	70									
U	PNP OPEN COLL	70									
B	PUSH-PULL PRO	70									
H	PUSH-PULL	70									

(§) Clock-wise output rotation (see shaft).



(§) Clock-wise output rotation (see shaft).



Tolerance between phases ± 25°, symmetry ± 15°

(§) Clock-wise output rotation (see shaft).



ELCIS s.r.l. Via Rosa Luxembourg 12/14 10093 COLLEGNO (TO) ITALY
Phone: +39 011 715577/78 a.r.
MAIL: ELCIS s.r.l. P.O.Box 90 10093 COLLEGNO (TO) ITALY

* <http://www.elcis.com>
* e-mail: info@elcis.com
* Fax: +39 011 712613

N.I.F.: B-87969416



GUEMISA

C/ Del Electrodo, 68 Oficina-23
28522 Rivas Vaciamadrid (Madrid)
Tfno.: 91 764 21 00 - info@guemisa.com

POSSIBLE OPTIONS				POSSIBLE CONNECTIONS									
CODE	DESCRIPTION	CODE	DESCRIPTION	CABLE								OUTPUT:	
L	Low temperature	K J M A G	Invert. phase A,B,Zero. Zero logic combination Impregnated electronic High temperature Tropicalization	CV								AX	
Y	Unbreakable disk											RAD	
B	Low torque ball bear.			CONNECTOR								OUTPUT:	
H	Different shaft Ø												
R	75 KHz frequency												
V	100 KHz frequency	CABLE END CONNECTOR								OUTPUT:			
X	Custom options	VM TM VL TL VD VH VH5 VI VE VK TK VN VH6 VM5 VM9 VS								AX			
		VD5	RAD										
		TERMINAL BOX								OUTPUT:			

ORDERING INFORMATION

POSSIBLE SHAFT Ø	STANDARD NPN	CABLE	CONNECTOR	CABLE END CONNECTOR
()	(K) NPN OPEN COLL	IP65		IP65 encoder output
()	(Q) NPN	(CV) 1 m long	()	(VM) 7c normal
()	(R) NPN OPEN COLL	()	()	(TM) 7c sealed
()	(P) PNP	()	()	(VL) 10c normal
(n) Ø n upon requ.	(U) PNP OPEN COLL		()	(TL) 10c sealed
	(B) PUSH-PULL PRO		()	(VD) 9c
	(H) PUSH-PULL	TERMINAL BOX	()	(VH) 12c anticlock.
	(N) DRIVER 26LS31	IP00	()	(VH5) 12c clock-wise
	(T) TTL 7404	()	()	(VI) 12c crimped
	(C) DRIVER 88C30		()	(VE) 5c
			()	(VK) 17c normal
			()	(TK) 17c sealed
			()	(VN) 12c
			()	(VH6) 12c clock-wise
			()	(VM5) 26c
			()	(VM9) 16c
			()	(VS) 12c
			()	(VD5) 9c screened
	(X) CUSTOM OPTION			

OPTIONS	MODEL	PULSES/REVOL. (1)	POWER SUPPLY	VERSION (2)	ELECTRONIC (2)	CONNECTION (3)	OUTPUT
	44S	500	5	BZ	N	CV	
			(Vcc)				
		1 ÷ 2540					
(L)	()		(5) 5 V ±5%	(M) Monodirectional			AX ()
(Y)	(K)		(824) 8÷24 V	(B) Bidirectional			RAD (R)
()	(J)		(1828) 18÷28 V	(BZ) Bidirectional + zero			
(B)	(M)		(815) 8÷15 V	(MZ) Monodirectional + zero			
(H)	(A)		(12) 12 V ±5%				
(R)	()		(24) 24 V ±5%				
(V)	()		(1230) 12÷30/12 V				
()	(G)		(8245) 8÷24/5 V				
()	()		(1030) 10÷30 V				
()	()		(18285) 18÷28/5 V				
(X)	()		(1530) 15÷30/15 V				

NOTE: FOR 88C30 MAX 15 Vdc

- (1) For further information see PULSES/REVOL. data sheet
 (2) For further information see ELECTRONIC data sheet
 (3) For further information see CONNECTION data sheet

Product manufactured according to ISO EN 9001, supplied with CHECKING and CONFORMITY declaration with CE mark and with TWO (2) YEARS WARRANTY starting from delivery date.

COPYRIGHT by ELCIS - Collegno (TO)

ELCIS company has the right to make any changing without previous notice.

data sheet II006 E00 page: 01. 44S 1/2



ELCIS s.r.l. Via Rosa Luxembourg 12/14 10093 COLLEGNO (TO) ITALY
 Phone: +39 011 715577/78 a.r.
 MAIL: ELCIS s.r.l. P.O.Box 90 10093 COLLEGNO (TO) ITALY

* <http://www.elcis.com>
 * e-mail: info@elcis.com
 * Fax: +39 011 712613