

INCREMENTAL
ENCODER


58

GENERAL PURPOSE ENCODER IN STANDARD 'SIZE 23' METALLIC CONTAINER,
WITH SQUARE MOUNTING FLANGE.

Family: **I**
page: 02. 58 1/2
data sheet . II 009 E0A

Sized draw standard version: CW

Measures without tolerance according to UNI ISO 2768-mk



TECHNICAL FEATURES AND POSSIBLE CONFIGURATIONS

- | | |
|--|---|
| <ul style="list-style-type: none"> - Base.....: ANODIZED ALUMINIUM (*) - Cover.....: VALOX 420 (*) - Weight.....: 330 g - Shaft.....: Ø 6 STAINLESS STEEL (*) - Max.rad/axial load.: 3 kg - IP output side.(°): see 'CONNECTION' of page 2 - IP shaft side.(°):> std. 64 sealed 66 low torq. 53 - opt. type (page 2):> standard Z B - Contin. max RPM(**):> 8000 3000 12000 - Starting torque gcm> 18 30 8 | <ul style="list-style-type: none"> - Ball bearings life...: 1,5 x 10⁹ revolutions - Impact resistance....: 50 G x 11ms - Vibration resistance.: 12 G (10 ÷ 2000 Hz) - Power supply.....: 5÷30V (see page 2) - Operating temperature: 0 ÷ 70 °C (*) - Storage temperature...: -30 ÷ 85 °C - N° of pulses/rev.....: 1 ÷ 25000 - Max frequency.....: 100 kHz (300 option) - Max consumptions mA...: std 120 line driver 180 (*) - Light source.....: LED with >= 100000 h life |
|--|---|

(°) IP according to CEI EN 60529, EN 60529, IEC 529


(*) custom options

(**) intermittent max RPM + 30% of continuous max RPM


ELECTRONICS

CODE	DESCRIPTION	mA	CODE	DESCRIPTION	mA	CODE	DESCRIPTION	mA	CODE	DESCRIPTION	mA
K	STANDARD NPN	10	N	DRIVER 26LS31	30	D	DISCRIMINAT.	70	Y	SINUSOID. 1Vpp	10
Q	NPN OPEN COLL	10	T	TTL 7404	10						
R	NPN OPEN COLL	70	C	DRIVER 88C30	20						
P	PNP	70	L	2x PUSH-P.PRO	70						
U	PNP OPEN COLL	70	M	2x PUSH-PULL	70						
B	PUSH-PULL PRO	70									
H	PUSH-PULL	70									


(S)




A (S)



25µs (S)



A (S)



Tolerance between phases ± 25°, symmetry ± 15°

(S) Clock-wise output rotation (see shaft).



ELCIS s.r.l. Via Rosa Luxembourg 12/14 10093 COLLEGNO (TO) ITALY
Phone: +39 011 715577/78 a.r.
MAIL: ELCIS s.r.l. P.O.Box 43 10093 COLLEGNO (TO) ITALY

* <http://www.elcis.com>
* e-mail: info@elcis.com
* Fax: +39 011 712613

N.I.F.: B-87969416



GUEMISA

C/ Del Electrodo, 68 Oficina-23
28522 Rivas Vaciamadrid (Madrid)
Tfno.: 91 764 21 00 - info@guemisa.com

POSSIBLE OPTIONS				POSSIBLE CONNECTIONS			
CODE	DESCRIPTION	CODE	DESCRIPTION	CABLE			
L	Low temperature	C	Low consumption	CW			
Y	Unbreakable disk	K	Invert. phase A,B,Zero.				
Z	Sealed ball bearing	J	Zero logic combination	CONNECTOR			
B	Low torque ball bear.	M	Impregnated electronic				
H	Different shaft Ø	A	High temperature	CM	SM	CL	SL
		P	Compressed air attack	CE		CD	CH
						CH5	CI
S	160 KHz frequency	G	Tropicalization	CABLE END CONNECTOR			
W	300 KHz frequency						
X	Custom options			VM	TM	VL	TL
				VE	VK	TK	VN
				VD5		VH	VH5
						VI	VS
				TERMINAL BOX			
				MS			

ORDERING INFORMATION

POSSIBLE SHAFT Ø	STANDARD NPN	CABLE	CONNECTOR	CABLE END CONNECTOR
()	(K) NPN OPEN COLL	IP65		IP65 encoder output
()	(Q) NPN			
()	(R) NPN OPEN COLL	() 1 m long	(CM) 7c norm. IP65	(VM) 7c normal
()	(P) PNP		(SM) 7c sealed IP66	(TM) 7c sealed
()	(U) PNP OPEN COLL		(CL) 10c norm. IP65	(VL) 10c normal
(n) Ø n upon requ.	(B) PUSH-PULL PRO		(SL) 10c sealed IP66	(TL) 10c sealed
()	(H) PUSH-PULL		(CD) 9c sub D IP63	(VD) 9c
()	(N) DRIVER 26LS31	TERMINAL BOX	(CH) 12c ccw IP67	(VH) 12c anticlock.
()	(T) TTL 7404	IP00	(CH5) 12c cw IP67	(VH5) 12c clock-wise
()	(C) DRIVER 88C30	(MS) Phoenix	(CI) 12c crimp. IP64	(VI) 12c crimped
()	(L) 2x PUSH-P.PRO		(CE) 5c miniat IP64	(VE) 5c
()	(M) 2x PUSH-PULL			(VK) 17c normal
()	(D) DISCRIMINAT.			(TK) 17c sealed
()	(Y) SINUSOID.1Vpp		(C4) 4c screw IP65	(VN) 12c
()	(X) CUSTOM OPTION		(CH6) 12c cw IP67	(VH6) 12c clock-wise
				(VM5) 26c
				(VM9) 16c
				(VS) 12c
				(VD5) 9c screened

OPTIONS	MODEL	PULSES/REVOL. (1)	POWER SUPPLY	VERSION (2)	ELECTRONIC (2)	CONNECTION (3)	OUTPUT
58	500	5	BZ	N	CW		
(L)	(C)	1 ÷ 25000	(Vcc)	(M) Monodirectional		AX	
(Y)	(K)		(5) 5 V ±5%	(B) Bidirectional		RAD	
(Z)	(J)		(824) 8÷24 V	(BZ) Bidirectional + zero		()	
(B)	(M)		(1828) 18÷28 V	(MZ) Monodirectional + zero		(R)	
(H)	(A)		(815) 8÷15 V				
()	(P)		(12) 12 V ±5%				
()	()		(24) 24 V ±5%				
(S)	(G)		(1230) 12÷30/12 V				
(W)	()		(8245) 8÷24/5 V				
()	()		(1030) 10÷30 V				
()	()		(18285) 18÷28/5 V				
(X)	()		(1530) 15÷30/15 V				

NOTE: FOR 88C30 MAX 15 Vdc

- (1) For further information see PULSES/REVOL. data sheet
 (2) For further information see ELECTRONIC data sheet
 (3) For further information see CONNECTION data sheet

Product manufactured according to UNI EN ISO 9001:2000, supplied with CHECKING and CONFORMITY declaration with CE mark and with TWO (2) YEARS WARRANTY starting from delivery date.

ELCIS company has the right to make any changing without previous notice.

data sheet II009E0A page: 02. 58

COPYRIGHT by ELCIS - Collegno (TO)



ELCIS s.r.l. Via Rosa Luxembourg 12/14 10093 COLLEGNO (TO) ITALY
 Phone: +39 011 715577/78 a.r.
 MAIL: ELCIS s.r.l. P.O.Box 43 10093 COLLEGNO (TO) ITALY

* http://www.elcis.com
 * e-mail: info@elcis.com
 * Fax: +39 011 712613