



| POSSIBLE             |                   | OPTIONS                        |                                                                                                                                                 | POSSIBLE CONNECTIONS |    |     |     |     |         |     |    |     |  |
|----------------------|-------------------|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----|-----|-----|-----|---------|-----|----|-----|--|
| CODE                 | DESCRIPTION       | CODE                           | DESCRIPTION                                                                                                                                     | CABLE                |    |     |     |     | OUTPUT: |     |    |     |  |
| L                    | Low temperature   | K<br>J<br>M<br>A<br>P<br><br>G | Invert. phase A,B,Zero.<br>Zero logic combination<br>Impregnated electronic<br>High temperature<br>Compressed air attack<br><br>Tropicalization | CW                   |    |     |     |     | RAD     |     |    |     |  |
| Y                    | Unbreakable disk  |                                |                                                                                                                                                 | CONNECTOR            |    |     |     |     | OUTPUT: |     |    |     |  |
| H                    | Different shaft Ø |                                |                                                                                                                                                 | CM                   | SM | CL  | SL  | CH  | RAD     |     |    |     |  |
|                      |                   |                                |                                                                                                                                                 | CABLE END CONNECTOR  |    |     |     |     | OUTPUT: |     |    |     |  |
| X                    | Custom options    |                                |                                                                                                                                                 | VM                   | TM | VL  | TL  | VD  | VH      | VH5 | VI | RAD |  |
|                      |                   | VE                             | VK                                                                                                                                              | TK                   | VN | VH6 | VM5 | VM9 | VS      |     |    |     |  |
|                      |                   |                                |                                                                                                                                                 | TERMINAL BOX         |    |     |     |     | OUTPUT: |     |    |     |  |
|                      |                   |                                |                                                                                                                                                 |                      |    |     |     |     |         |     |    |     |  |
| ORDERING INFORMATION |                   |                                |                                                                                                                                                 |                      |    |     |     |     |         |     |    |     |  |

### ORDERING INFORMATION

| POSSIBLE SHAFT Ø   | POSSIBLE OPTIONS  | CABLE         | CONNECTOR            | CABLE END CONNECTOR  |
|--------------------|-------------------|---------------|----------------------|----------------------|
| ( )                | ( ) STANDARD NPN  | IP66          |                      | IP65 encoder output  |
| ( )                | (K) NPN OPEN COLL | (CW) 1 m long | (CM) 7c norm. IP64   | (VM) 7c normal       |
| ( )                | (Q) NPN           | ( )           | (SM) 7c sealed IP66  | (TM) 7c sealed       |
| ( )                | (R) NPN OPEN COLL | ( )           | (CL) 10c norm. IP64  | (VL) 10c normal      |
| ( )                | (P) PNP           | ( )           | (SL) 10c sealed IP66 | (TL) 10c sealed      |
| ( )                | (U) PNP OPEN COLL |               | (CH) 12c ccw IP67    | (VD) 9c              |
| (n) Ø n upon requ. | (B) PUSH-PULL PRO | TERMINAL BOX  |                      | (VH) 12c anticlock.  |
| ( )                | (H) PUSH-PULL     | IP00          |                      | (VH5) 12c clock-wise |
| ( )                | (N) DRIVER 26LS31 | ( )           |                      | (VI) 12c crimped     |
| ( )                | (T) TTL 7404      |               |                      | (VE) 5c              |
| ( )                | (C) DRIVER 88C30  |               |                      | (VK) 17c normal      |
| ( )                | (L) 2x PUSH-P.PRO |               |                      | (TK) 17c sealed      |
| ( )                | (M) 2x PUSH-PULL  |               |                      | (VN) 12c             |
| ( )                | (D) DISCRIMINAT.  |               |                      | (VH6) 12c clock-wise |
| ( )                | (Y) SINUSOID.1Vpp |               |                      | (VM5) 26c            |
| ( )                | (X) CUSTOM OPTION |               |                      | (VM9) 16c            |
| ( )                |                   |               |                      | (VS) 12c             |
| ( )                |                   |               |                      | (VD5) 9c screened    |

  

| OPTIONS | MODEL | PULSES/REVOL. (1) | POWER SUPPLY      | VERSION (2)                 | ELECTRONIC (2) | CONNECTION (3) | OUTPUT |
|---------|-------|-------------------|-------------------|-----------------------------|----------------|----------------|--------|
| 120     | 500   | 5                 | BZ                | N                           | CW             | R              |        |
| (L)     | (Y)   | 1 ÷ 2540          | (Vcc)             | (M) Monodirectional         |                |                | ( )    |
| ( )     | ( )   |                   | (5) 5 V ±5%       | (B) Bidirectional           |                |                | (R)    |
| ( )     | ( )   |                   | (824) 8÷24 V      | (BZ) Bidirectional + zero   |                |                |        |
| ( )     | ( )   |                   | (1828) 18÷28 V    | (MZ) Monodirectional + zero |                |                |        |
| ( )     | ( )   |                   | (815) 8÷15 V      |                             |                |                |        |
| (H)     | (A)   |                   | (12) 12 V ±5%     |                             |                |                |        |
| ( )     | (P)   |                   | (24) 24 V ±5%     |                             |                |                |        |
| ( )     | ( )   |                   | (1230) 12÷30/12 V |                             |                |                |        |
| ( )     | (G)   |                   | (8245) 8÷24/5 V   |                             |                |                |        |
| ( )     | ( )   |                   | (1030) 10÷30 V    |                             |                |                |        |
| ( )     | ( )   |                   | (18285) 18÷28/5 V |                             |                |                |        |
| ( )     | ( )   |                   | (1530) 15÷30/15 V |                             |                |                |        |
| (X)     | ( )   |                   | ( )               |                             |                |                |        |

  

Product manufactured according to ISO EN 9001, supplied with CHECKING and CONFORMITY declaration with CE mark and with TWO (2) YEARS WARRANTY starting from delivery date.

NOTE: FOR 88C30 MAX 15 Vcc

- (1) For further information see PULSES/REVOL. data sheet  
 (2) For further information see ELECTRONIC data sheet  
 (3) For further information see CONNECTION data sheet

ELCIS company has the right to make any changing without previous notice.

data sheet II091 E00 page: 03.120

1/2



ELCIS s.r.l. Via Rosa Luxembourg 12/14 10093 COLLEGNO (TO) ITALY  
 Phone: +39 011 715577/78 a.r.  
 MAIL: ELCIS s.r.l. P.O.Box 90 10093 COLLEGNO (TO) ITALY

\* <http://www.elcis.com>  
 \* e-mail: [info@elcis.com](mailto:info@elcis.com)  
 \* Fax: +39 011 712613