

C\ Del Electrodo, 68 Oficina-23
28522 Rivas Vaciamadrid (Madrid)
Tfno.: 91 764 21 00 - info@quemisa.com

POSSIBLE OPTIONS		POSSIBLE CONNECTIONS	
CODE	DESCRIPTION	CODE	DESCRIPTION
L	Low temperature	K J M A G	Invert. phase A,B,Zero. Zero logic combination Impregnated electronic High temperature Tropicalization
Y	Unbreakable disk		
Z	Sealed ball bearing		
B	Low torque ball bear.		
H	Different shaft Ø		
S	160 KHz frequency		
W	300 KHz frequency		
X	Custom options		

CABLE		OUTPUT:	
CV		AX RAD	
CONNECTOR		OUTPUT:	
CH CH5		AX RAD	
CH6			
CABLE END CONNECTOR		OUTPUT:	
VM VE VD5	TM VK TK	VL TK VN	VD VH6 VM5
VH VM5 VM9		VI VS	
TERMINAL BOX		OUTPUT:	

ORDERING INFORMATION			
----------------------	--	--	--

ORDERING INFORMATION

POSSIBLE SHAFT Ø	STANDARD NPN	CABLE	CONNECTOR	CABLE END CONNECTOR
()	(K) NPN OPEN COLL	IP65		IP65 encoder output
()	(Q) NPN	(CV) 1 m long	()	(VM) 7c normal
()	(R) NPN OPEN COLL	()	()	(TM) 7c sealed
()	(P) PNP	()	()	(VL) 10c normal
(n) Ø n upon requ.	(U) PNP OPEN COLL		()	(TL) 10c sealed
	(B) PUSH-PULL PRO		()	(VD) 9c
	(H) PUSH-PULL	TERMINAL BOX	(CH) 12c ccw IP67	(VH) 12c anticlock.
	(N) DRIVER 26LS31	IP00	(CH5) 12c cw IP67	(VH5) 12c clock-wise
	(T) TTL 7404		()	(VI) 12c crimped
	(C) DRIVER 88C30		()	(VE) 5c
			()	(VK) 17c normal
			()	(TK) 17c sealed
	(Y) SINUSOID.1Vpp		(CH6) 12c cw IP67	(VN) 12c
	(X) CUSTOM OPTION			(VH6) 12c clock-wise
				(VM5) 26c
				(VM9) 16c
				(VS) 12c
				(VD5) 9c screened

OPTIONS	MODEL	PULSES/REVOL. (1)	POWER SUPPLY	VERSION (2)	ELECTRONIC (2)	CONNECTION (3)	OUTPUT
(L)	68LL	500	5	BZ	N	CV	R
(Y)		1 ÷ 25000	(Vcc)				
(Z)			(5) 5 V ±5%	(M) Monodirectional			AX ()
(B)			(824) 8÷24 V	(B) Bidirectional			RAD (R)
(H)			(1828) 18÷28 V	(BZ) Bidirectional + zero			
()			(815) 8÷15 V	(MZ) Monodirectional + zero			
()			(12) 12 V ±5%				
(S)			(24) 24 V ±5%				
(W)			(1230) 12÷30/12 V				
()			(8245) 8÷24/5 V				
(X)			(1030) 10÷30 V				
			(18285) 18÷28/5 V				
			(1530) 15÷30/15 V				

NOTE: FOR 88C30 MAX 15 Vdc

- (1) For further information see PULSES/REVOL. data sheet
 (2) For further information see ELECTRONIC data sheet
 (3) For further information see CONNECTION data sheet

Product manufactured according to UNI EN ISO 9001:2000,
 supplied with CHECKING and CONFORMITY
 declaration with CE mark and with TWO (2) YEARS
 WARRANTY starting from delivery date.

ELCIS company has the right to make any changing without previous notice.

data sheet II065 E0A page: 08. 68LL 1/2



ELCIS s.r.l. Via Rosa Luxembourg 12/14 10093 COLLEGNO (TO) ITALY
 Phone: +39 011 715577/78 a.r.
 MAIL: ELCIS s.r.l. P.O.Box 43 10093 COLLEGNO (TO) ITALY

* <http://www.elcis.com>
 * e-mail: info@elcis.com
 * Fax: +39 011 712613